DIGITUS® RJ45 Modular Coupler, unshielded

AT-A 8/8

EAN 4016032066569



CAT 5e Modular Coupler, unshielded RJ45 to RJ45, color white

The unshielded modular RJ couplers from DIGITUS® are available as RJ12, 6P6C or RJ45, 8P8C version. The assignment is "1:1".

- Technical properties:
- Housing material: ABS
- Contacts coating: Nickel, gold-plated 0.5 µ
- Shielding: Tinned bronze
- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: ⊠ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug

Attributes

- Category: CAT 5e

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1000	9.00	61.00	31.00	38.00	71,858.00
Packaging Unit Inside	100	0.90	30.00	18.00	6.00	3,240.00
Packaging Unit Single	1	0.01	5.00	3.00	2.00	30.00
Net single without Packaging	1	0.01	3.70	2.30	1.50	0.00

Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com