DIGITUS® CAT 5e SF/UTP □□□□-□□□□□□

DK-1532-030

EAN 4016032199670



CAT 5e SF-UTP patch cord, PVC AWG 26/7, length 3 m, color grey

DIGITUS® Category 5e Class D patch cables are manufactured and tested in accordance with the ISO/IEC 11801 and DIN EN 50173 CAT 5e standards. They ensure that the cable installation complies with the ISO & EN channel specifications and deliver outstanding performance in DIGITUS® CAT 5e cabling. Performance has been tested up to 100 MHz, including performance characteristics such as near-end crosstalk (NEXT). DIGITUS® patch cables have been specially developed to fully meet all requirements across various application areas. Each cable is equipped with an injection-molded kink-protection sleeve with strain relief. In addition, the sleeve features a latch protection mechanism that prevents the cables from getting snagged and the latch from breaking off the connector. The blue color of the connectors makes it easy to identify Category 5e cables.

□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□ □ □□□□□□□□□ □□□□□□ □□□ □□□□□□ □□□□□.

- 2 □□□□□□□□ RJ45 (8P8C)
- □□□□□□□□□ □ □□□□□□□□ □□ □□□□□□□, □□□□□□□□□□ □ □□□□□□□□□
- □□□□□□ □□□□□□ □□ □□□□□□□□□

Attributes

- Assortment: Twisted Pair Patch Cables
- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: DIGITUS Polybag
- Category: CAT 5e
- Shielding: SF-UTP, foil and braid shielding
- Length: 3 m
- Color: grey
- Jacket: PVC
- Slim Version: no
- Structure: 4 x 2 AWG 26/7, twisted pair
- Flat Version: no

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	9.10	38.00	29.00	32.00	35,264.00
Packaging Unit Inside	10	0.91	35.00	21.00	7.00	5,145.00
Packaging Unit Single	1	0.09	26.00	16.00	2.50	1,040.00
Net single without Packaging	1	0.08	300.00	1.20	1.30	0.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable

- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com