

## DIGITUS® DIGITUS

DN-19 PB-4U-SW  
EAN 4016032250371



### 4U wall mounting patch bracket, 195x505x250 mm adjustable depth, stackable, black (RAL 9005)

DIGITUS 4U wall mounting patch bracket, 195x505x250 mm adjustable depth, stackable, black (RAL 9005) 483 mm (19")

- 4U wall mounting patch bracket, 195x505x250 mm adjustable depth, stackable, black (RAL 9005)
- 483 mm (19")

#### Attributes

- Cabinet type: Wall mounting cabinet
- Color: black, RAL 9005

- Front door: without
- Load capacity: 15 kg

Side panels: Both sides  
Units: 4

- Protection class: without
- Mounted: no

#### Package contents

- Fastening material for stacking

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	5	18.20	23.50	55.50	22.00	28,693.50
Packaging Unit Inside	1	3.64	20.50	53.00	4.00	4,346.00
Packaging Unit Single	1	3.64	20.50	53.00	4.00	4,346.00
Net single without Packaging	1	0.00	25.00	50.50	19.50	0.00

#### More images:





### Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)