

DIGITUS® SOHO, – 5

DN-19 07-U-S-SW
EAN 4016032257592



7U wall mounting cabinet, SoHo, unmounted 370x540x400 mm, glass front door, black (RAL 9005)

- IP20 protection class
- Front door: Glass door, single opening
- Side panels: Both sides
- Units: 7
- Width: 540 mm
- IP protection class: IP20

- Cabinet type: Wall mounting cabinet
- Color: black, RAL 9005
- Depth: 400 mm
- Front door: Glass door, single opening
- Side panels: Both sides
- Units: 7
- Width: 540 mm
- IP protection class: IP20

Package contents

- Installation set (screws, cage nuts, washers)
- 2x keys
- 1x quick start guide

Attributes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	13.20	45.00	59.00	19.00	50,445.00
Packaging Unit Inside	1	13.20	45.00	59.00	19.00	50,445.00
Packaging Unit Single	1	13.20	45.00	59.00	19.00	50,445.00
Net single without Packaging	1	12.00	40.00	54.00	37.50	21,070.00

Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.

- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com