

DIGITUS DIGITUS блок электрических розеток в алюминиевом корпусе, с выключателем, 7 розеток

DN-95402
EAN 4016032266402



1U Aluminum PDU, rackmountable, 7x safety outlet 16A, 4000W, 250VAC 50/60Hz, switch

Распределители электропитания (РЭ) DIGITUS® – идеальное решение для сетевого оборудования 19" или серверной комнаты. Благодаря возможности настенного крепления и питания от сети 220-240 В 50-60 Гц, распределитель питания DIGITUS® предлагает сочетание наилучших технических характеристик и эффективности. 19-дюймовый крепеж обеспечивает надежное крепление на рейках в серверной комнате. Допускается как вертикальная, так и горизонтальная установка каждого РЭ. Кроме того, в зависимости от устройства серверной комнаты он может устанавливаться лицевой частью вверх или вниз.

Надежное профессиональное питание для 19-дюймового оборудования

- 7 розеток 250VA 50/6 Гц / 16 А / 4000 Вт
- Алюминиевый профиль
- 2 угловых профиля для монтажа в шкаф
- Кабель H05VV-F 35 сечением 1,5 мм² (2 м) с вилкой

- Пластиковые компоненты из АБС-пластика UL-94V-0
- Заземление на алюминиевый профиль
- Розетки с защитным контактом, повернутые на 35°
- Выключатель с подсветкой - защищён от случайного отключения
- Выключатель с подсветкой - защищён от случайного отключения

Attributes

- Additional Features: Power switch
- Current: 16 A
- Input Plug: CEE7/7
- Installation: Desktop, Rack 0U, Rack 1U
- Outlets: CEE 7/3
- Phase: 1ph
- Power: 3,6 kVA
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 10 | 10.50 | 51.00 | 49.50 | 41.50 | 104,767.00 |
| Packaging Unit Inside | 1 | 1.05 | 6.70 | 50.00 | 9.10 | 3,048.50 |
| Packaging Unit Single | 1 | 1.05 | 6.70 | 50.00 | 9.10 | 3,048.50 |
| Net single without Packaging | 1 | 0.77 | 4.40 | 48.20 | 4.40 | 0.00 |

More images:



**Aluminum Outlet Strip with Switch,
7 Safety Outlets,
2m Supply Safety Plug**

Safety notes

- This product is not intended for unsupervised use by children or persons under their care!
- Prevent higher humidity or temperatures than those specified in the data sheet - Avoid moisture, dust or vapors, solvents, flammable gases.
- Multiple sockets are not designed for permanent use with heavy loads!
- Multiple sockets must not be cascaded (avoid stringing together several multiple sockets).
- The maximum connected load must not be exceeded.
- Defective multiple sockets must be taken out of service immediately and disposed of in an environmentally friendly manner.
- In the event of a fault, take the product out of operation and contact a qualified electrician.
- Do not open the product.
- Disconnect the product from the power supply before cleaning. Do not use any aggressive or abrasive cleaning agents for cleaning.
- The ingress of liquids can lead to a short circuit.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com