

# DIGITUS® CAT 5e, Class D, RJ45 Modular Coupler

DN-93901

EAN 4016032266488



### CAT 5e Modular Coupler, shielded RJ45 to RJ45

The modular CAT5e Class D coupler from DIGITUS® consists of two shielded RJ45 female ports. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 µ
- Shielding: Tinned bronze
- PCB:FR4, UL 94V-0

- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug

#### Attributes

- Category: CAT 5e

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1000	9.00	61.00	31.00	38.00	71,858.00
Packaging Unit Inside	100	0.90	30.00	18.00	11.50	6,210.00
Packaging Unit Single	1	0.01	1.20	6.00	9.00	64.80
Net single without Packaging	1	0.01	3.70	1.10	2.20	0.00

### Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)