

DIGITUS® Pigtaills LC Simplex OS2 de cor sólida

DK-29332-02

EAN 4016032280170



Conjunto de pigtaills de fibra ótica, 12 peças, LC, SM OS2 09/125 µ tampão solto, código de cor DIN IEC 304, 2 m

Os pigtaills de fibra ótica DIGITUS® estão disponíveis nas versões LC Simplex, SC Simplex e ST Simplex e oferecem-lhe um excelente desempenho e qualidade de ligação para a sua rede com as classes OS2, OM2, OM3 e OM4. O conector está em conformidade com a norma IEC 61754-4 2002 e está equipado com uma virola de cerâmica de zircónio. Os conjuntos de fibras coloridas estão codificados por cores de acordo com a norma IEC 304 (branco, violeta, turquesa, preto, vermelho, rosa, laranja, cinzento, verde, amarelo, castanho, azul).

Padrões orientados para o futuro e qualidade de topo de gama para a sua rede.

- Simplex OS2 09/125 µ 2 m
- Conectores de acordo com a norma IEC 61754-4 2002
- Temperatura de funcionamento: -25 °C ... +80 °C
- Gama de temperaturas de transporte e armazenamento: -20 °C ... +65 °C

- Perda de inserção MM PC: máx. 0,4 dB
- Perda de retorno MM PC: > 25 dB
- Virola de cerâmica de zircónio
- Dimensões do revestimento secundário: Ø 0,9 ± 0,1 mm
- Revestimento primário: acrilatos; Ø 250 ± 15 µm
- Conjuntos de fibras coloridas de acordo com a norma IEC 304 nas cores: Branco, violeta, turquesa, preto, vermelho, rosa, laranja, cinzento, verde, amarelo, castanho, azul
- 12 unidades como unidade de embalagem
- Tampão solto

Attributes

- Boot: single-color
- Connector 1: LC
- Fiber class: OS2
- Fiber diameter: 9/125µ
- Mode: Singlemode
- Length: 2 m

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	160	8.20	60.00	38.00	32.00	72,960.00
Packaging Unit Inside	20	1.03	18.00	19.50	14.00	4,914.00
Packaging Unit Single	1	0.05	0.50	20.00	30.00	300.00
Net single without Packaging	1	0.03	17.00	17.00	0.50	0.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com