

## DIGITUS® USB 2.0

AK-300202-030-S  
EAN 4016032283195



### USB 2.0 extension cable, type A M/F, 3.0m, USB 2.0 conform, bl

Das Produkt ist ein USB-Verlängerungskabel (USB-Verlängerungskabel A), das die Datenübertragung mit einer Geschwindigkeit von bis zu 480 Mbit/s (High-Speed) ermöglicht. Das Kabel ist 3,0 m lang und besteht aus hochwertigem Kupferdraht (AWG 28) mit einer Nickelplattierung der Kontakte. Die Stecker sind aus Kunststoff gefertigt und haben eine schwarze Abdeckung. Das Kabel ist doppelt geschichtet, um elektromagnetische Störungen zu reduzieren.



#### Attributes

- Assortment: USB Cables
- AWG: 28
- Color cable: black
- Color connector: black

- Connector 1: USB A, plug
- Connector 2: USB A, jack
- Connector surface: nickel-plated
- Data transfer rate: up to 480 Mbit/s (High-Speed)
- Hoods: molded
- USB compliance: USB 2.0
- Wire material: CU
- Length: 3 m
- Shielding: Double shielding

| Logistics                    |              |             |            |            |             |                 |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| Packaging Unit Carton        | 200          | 13.38       | 32.00      | 45.00      | 25.00       | 36,000.00       |
| Packaging Unit Inside        | 10           | 0.67        | 18.00      | 33.00      | 6.00        | 3,564.00        |
| Packaging Unit Single        | 1            | 0.07        | 14.00      | 25.00      | 1.10        | 385.00          |
| Net single without Packaging | 1            | 0.06        | 10.00      | 14.00      | 1.00        | 0.00            |

#### More images:





### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)