# DIGITUS® □□□□□□□□□□□□□□□ □□□□□□ USB 2.0

**AK-300101-010-S**

**EAN 4016032283652**



**USB 2.0 connection cable, type A M/M, 1.0m, USB 2.0 conform, bl**

□□□□ □□□□□□□□□□□□□ □□□□□□□□ USB-□□□□□□□□□□□ (□ □□□□□□□□□□ □□□□□ □) □ USB-□□□□□□ (□□□□□□□□□□, □□□, □□□□□□□□□□ □□□□ USB-□□□□□□□□□□□□□□□). □□□□□□□□□ □□□□□□□□□□ □□□□□□□□□□□□□□ □□□□□□□□□□ □ □□□□□□□□ □□□□□□□□□□□□□□ □□□□□□□□□ □□□□□□□□□□□□□□□□



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com