DIGITUS® DVI extender via CAT5 / CAT6

DS-54101

EAN 4016032285694



DVI Video Extender over CAT5 up to 70m (CAT5, UTP), max. res. 1920X1200@60Hz

The DVI Cat.5 / Cat.6 Extender extends the transmission distance of your PC DVI connection to up to 70m via a simple Cat5 cable. The possible resolution depends on the selected distance.

Extends a DVI signal up to 70 meters

- DVI-D extension via Cat.5 / Cat.6 cable
- Supports a maximum resolution of 1920x1200 pixels at a distance of 50m
- Supports a maximum extension of up to 70m at a resolution of 800x600 pixels
- No external power supply required
- Compression: Uncompressed

Attributes

- HDTV-norma: Full HD
- rezolucija maks.: 1920 x 1200 piksela, 60 Hz
- Kategorija: CAT 5e
- KVM: Ne
- PoE (napajanje preko Etherneta): Ne
- Razmak: 50 m
- Tehnologija prijenosa: CAT

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	10.58	33.50	37.00	27.50	34,086.20
Packaging Unit Inside	1	0.11	4.90	8.60	6.30	265.48
Packaging Unit Single	1	0.11	5.00	8.50	6.00	255.00
Net single without Packaging	1	0.06	5.60	4.00	2.30	187.50

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:





Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com