

# DIGITUS® DisplayPort, 1m

AK-340100-010-S  
EAN 4016032288916



**DisplayPort connection cable, DP M/M, 1.0m, w/interlock, Ultra HD 4K, bl**

Digitus DisplayPort connection cable, DP M/M, 1.0m, w/interlock, Ultra HD 4K, bl. This cable is designed for high-resolution video and audio transmission. It features a 1.0m length and is compatible with Ultra HD 4K displays. The cable is black and has a snap fastener interlock for secure connections. It is suitable for use in CAD/CAM, GIS, and 3D applications. The cable is made of CCS wire material and has triple shielding for signal integrity. The connectors are black and have a nickel-plated surface. The cable is molded and has a length of 1m. It is not an Active Optical Cable (AOC). The cable is suitable for use in HDTV Standard: Ultra HD 4K. The cable is suitable for use in Hoods: molded. The cable is suitable for use in Interlock: Snap fastener. The cable is suitable for use in Wire material: CCS. The cable is suitable for use in Length: 1m. The cable is suitable for use in AOC - Active Optical Cable: no. The cable is suitable for use in Shielding: triple shielding.

- Resolution: 4K/2K @ 60 Hz
- Resolution: 4K/2K @ 24 Hz, 4K/2K @ 30 Hz, 4K/2K @ 60 Hz
- Resolution: 4096 x 2160p; 1920 x 1080p

**Attributes**

- Assortment: DisplayPort Cables
- AWG: 30
- Color cable: black

- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Wire material: CCS
- Length: 1 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	100	8.00	50.00	33.00	22.00	36,300.00
Packaging Unit Inside	10	0.80	2.00	14.00	22.00	616.00
Packaging Unit Single	1	0.08	22.00	14.00	2.50	770.00
Net single without Packaging	1	0.06	14.00	12.50	2.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)