

DIGITUS® Cabo de extensão DisplayPort, DP

AK-340200-020-S
EAN 4016032289142



Cabo de extensão DisplayPort, tipo DP St/Bu, 2,0 m, c/interbloqueio, compatível com DP 1.2, preto

Este cabo áudio/vídeo digital HD de elevado desempenho é utilizado para prolongar as ligações DisplayPort existentes, por exemplo, entre a placa gráfica e o monitor.

Transporta sinais de áudio/vídeo HD de elevado desempenho em distâncias mais longas

- Suporta até 1080p com 60 Hz
- Resolução de vídeo suportada: 4K (3840x2160)@60Hz e Full HD (1920x1080)@120Hz
- Modos de transmissão suportados: RBR, HBR, HBR2
- Largura de banda máxima: 21,6 Gbps
- Versão HBR/modo de transferência: HBR2 (5,40 Gbit/s por via)
- Versão HDCP: HDCP 1.3

Attributes

- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, jack
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 2 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	70	12.00	50.00	32.00	22.00	35,200.00
Packaging Unit Inside	5	0.86	22.00	15.00	2.50	825.00
Packaging Unit Single	1	0.17	22.00	15.00	2.50	825.00
Net single without Packaging	1	0.17	0.00	0.00	0.00	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com