

DIGITUS® Adaptador / conversor DisplayPort

AK-340400-001-S

EAN 4016032289241



Cabo adaptador DisplayPort, tipo DP - HDMI tipo A St/Bu, 0.08m,c/interbloqueio DP 1.1a comp, pb

Este adaptador/conversor de vídeo HD e áudio digital é ideal para ligar um computador portátil ou computador com uma interface DP a um monitor HDMI, projetor, monitor LCD/TFT, televisor LED ou plasma através de um cabo HDMI.

Reduz a carga na interface.

- Suporta até 1080p com 60 Hz
- Suporta o modo duplo DP++
- Largura de banda máxima: 6,75 Gbps
- Versão HBR/modo de transferência: HBR1 (2,70 Gbit/s por via)

Attributes

- Assortment: DisplayPort Cables
- AWG: 28

- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: HDMI type A, jack
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Resolution max.: 1920 x 1080 Pixel, 60Hz
- Wire material: CU
- Length: 0.08 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	250	9.95	50.00	32.00	21.00	33,600.00
Packaging Unit Inside	10	0.40	40.60	40.60	6.60	10,879.20
Packaging Unit Single	1	0.04	11.50	9.50	21.00	2,294.25
Net single without Packaging	1	0.03	15.00	2.10	1.20	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com