

DIGITUS® Adaptador / conversor DisplayPort

AK-340401-001-S

EAN 4016032289265



Cabo adaptador DisplayPort, tipo DP – DVI (24+5) St/Bu, 0,15m, c/interlock, compatível com DP 1.1, preto

Este adaptador/conversor digital HD é ideal para ligar um computador portátil ou computador com uma interface DP a um monitor DVI, projetor ou monitor LCD/TFT através de um cabo DVI.

Perfeito para transmissões de vídeo, jogos ou ampliação da estação de trabalho

- Suporta até 1080p com 60 Hz
- Suporta sinais digitais Full HD e DVI-D de ligação simples. (18+1)
- Núcleos de cobre, folha e trança blindados para robustez e uma ligação fiável
- Plug and play, sem necessidade de driver adicional
- Atenção! A tomada DVI suporta 24+5 conectores, mas apenas transmite sinais DVI-D de ligação única 18+1 em resolução Full HD.
- Suporta DisplayPort 1.1
- Largura de banda: 6,75 Gbps (2,25 por canal, 225 MHz)
- Profundidade de cor: 36 bits (12 bits por canal)
- Fonte de alimentação através do DisplayPort
- Entrada: Conector DisplayPort, 20 pinos
- Saída: tomada DVI, (24+5)
- Resoluções: 480i, 576i, 1080i, 480p, 576p, 720p, 1080p (50 / 60 Hz)
- Temperatura de funcionamento: 0°C a +45°C
- Humidade de funcionamento: 10% a 80% HR (sem condensação)

- Temperatura de armazenamento: -10°C a +80°C
- Humidade de armazenamento: 5% a 90% HR (sem condensação)
- Consumo de energia: 300 mW
- Comprimento total do cabo: 15 cm
- Cor: preto

Attributes

- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DVI-I, (24+5), jack
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 0.15 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	9.70	38.10	30.20	31.10	35,784.30
Packaging Unit Inside	10	0.49	40.60	40.60	8.10	13,351.70
Packaging Unit Single	1	0.05	20.00	15.00	1.62	486.00
Net single without Packaging	1	0.04	24.50	4.50	1.50	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com