

DIGITUS® Cabo de ligação DisplayPort, 2m

AK-340102-020-W
EAN 4016032289333



Cabo de ligação DisplayPort, tipo mini DP - DP St/St, 2.0m, c/ bloqueio, Full HD, DP 1.1a conf., branco

Este cabo de áudio e vídeo digital HD de elevado desempenho é ideal para ligar um MacBook, MacBook Air, MacBook Pro, iMac, Mac mini e Mac Pro a um monitor, projetor ou monitor LCD/TFT com interface DP, por exemplo.

Ideal para ligar dispositivos móveis a ecrãs

- Suporta 1080p com 30 Hz
- Resolução máxima de vídeo suportada: 1920 x 1080 p com 60 Hz
- Modos de transmissão suportados: RBR, HBR, HBR2
- Largura de banda máxima: 10,8 Gbps
- Versão HBR/modo de transferência: HBR1 (2,70 Gbit/s por via)
- Versão HDCP: HDCP 1.3


Attributes

- Assortment: DisplayPort Cables

- AWG: 32
- Color cable: white
- Color connector: white
- Connector 1: Mini DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 2 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	60	8.10	40.00	30.00	18.00	21,600.00
Packaging Unit Inside	10	1.35	35.00	43.00	1.50	2,257.50
Packaging Unit Single	1	0.14	25.00	14.00	3.00	1,050.00
Net single without Packaging	1	0.12	0.00	0.00	0.00	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com