

# DIGITUS® Acoplamento modular CAT 6A, blindado

DN-93905

EAN 4016032291824



### Acoplamento modular CAT 6A, totalmente blindado RJ45 para RJ45

Cumpra os requisitos de canal de acordo com a norma ISO/IEC 11801 para a classe EA até 500 MHz

- 2 x tomada RJ45
- Atribuição: 1:1
- Versão blindada
- Material da caixa: Folha de latão - niquelada brilhante

- Material da placa de circuito impresso: FR4, 1,2 mm de espessura
- Material dos contactos: Bronze fosforoso
- Revestimento Contactos: Niquel, banhado a ouro 0,6 µ
- Ciclos de acasalamento: ≥ 750
- Temperatura de funcionamento: -10 °C ~ +50 °C

#### Attributes

- Category: CAT 6A

### Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	500	10.10	54.50	34.50	13.50	25,383.40
Packaging Unit Inside	50	1.01	25.00	23.00	7.00	4,025.00
Packaging Unit Single	1	0.02	2.00	7.00	12.00	168.00
Net single without Packaging	1	0.01	1.50	2.50	4.00	0.00

### More images:



**Safety notes**

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)