DIGITUS® HDMI High Speed connection cable, with amplifier

AK-330105-150-S

EAN 4016032295808



HDMI High Speed Connection Cable, Type A, w/amp. M/M, 15.0m, Full HD, gold, bl

This Full HD (1080p) and 3D-compatible cable with active amplifier is used to connect audio/video devices, such as Blu-ray players, games consoles, etc., to a TV, monitor or PC.

Full HD and 3D compatible

- HDMI 1.3 feature support
- Supports up to 1080p with 60 Hz
- Supported video formats: 1080p @24 Hz, 1080p @30 or 60@Hz; 3D
- Supported audio formats: DVD-Audio, SACD, Dolby Digital Plus, TrueHD and dts-HD
- 3D support
- Important: This active HDMI cable is directional. An incorrect connection direction will result in no signal.

Attributes

- Asortiman: HDMI kabeli
- AWG: 28
- HDMI-norma: HDMI velike brzine
- HDTV-norma: Full HD
- Kabel u boji: crni
- Kapice: ukalupljeno
- Konektor 1: HDMI tip A, utikač
- Konektor 2: HDMI tip A, utikač
- Konektor u boji: crni
- Materijal žice: CU
- Površina konektora: pozlaćeno
- rezolucija maks.: 1920 x 1080 piksela, 60 Hz
- Duljina: 15 m
- AOC - aktivni optički kabel: Ne
- oklop: dvostruki oklop

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	15	15.68	50.50	32.00	21.50	34,744.00
Packaging Unit Inside	1	1.05	19.00	18.00	8.00	2,736.00
Packaging Unit Single	1	1.05	19.00	18.00	8.00	2,736.00
Net single without Packaging	1	0.96	17.00	16.50	7.50	0.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:







Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com