

# DIGITUS Adaptador HDMI, com ângulo de 90°

AK-330502-000-S EAN 4016032296164



## HDMI adapter, type A, 90ø angled M/F, Ultra HD 60p, bl, gold

Este cabo Full HD (1080p) e 3D pode ser utilizado para garantir uma conexão melhor de cabos HDMI normais com conectores diretos, caso falte espaço. Para evitar que o cabo seja entortado mais que o necessário, por exemplo.

### Compatível com 4K/Ultra HD e 3D + ligação Ethernet

• Suporta até 4K/2K com 60Hz

#### Attributes

· Assortment: HDMI Cables

- · Color connector: black
- Connector 1: HDMI type A, plug
- Connector 2: HDMI type A, jack
- · Connector surface: nickel-plated
- HDTV Resolution max.: 3840 x 2160 Pixel, 60Hz
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Packaging: Polybag
- AOC Active Optical Cable: no
- Shielding: single shielding

| Logistics                    |                 |                |               |               |                |           |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|-----------|
|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³       |
| Packaging Unit Carton        | 250             | 4.50           | 32.00         | 30.00         | 22.00          | 21,120.00 |
| Packaging Unit Inside        | 50              | 0.90           | 4.00          | 18.00         | 25.00          | 1,800.00  |
| Packaging Unit Single        | 1               | 0.02           | 1.50          | 7.00          | 7.50           | 78.75     |
| Net single without Packaging | 1               | 0.00           | 0.00          | 0.00          | 0.00           | 0.00      |

# Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- · Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

#### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com