



DIGITUS DVI extension cable

AK-320200-030-S
EAN 4016032298489



DVI extension cable, DVI(24+1), 2x ferrit M/F, 3.0m, DVI-D Dual Link, bl

This digital, Full HD suitable DVI cable (Dual Link), is used to extend existing connections of audio/video equipment or cables with DVI(24+1) interface, such as between PC, notebook, monitor, TV or a projector, for example.

Plné HD, duální propojení

- Support up to 2560 x 1600 pixel with 30Hz

Attributes

- Assortment: DVI Cables
- AWG: 30

- Color cable: black
- Color connector: black
- Connector 1: DVI-D, (24+1), plug
- Connector 2: DVI-D, (24+1), jack
- Connector surface: nickel-plated
- Ferrite filter: 2 x ferrite beads
- HDTV Resolution max.: 2560 x 1600 Pixel, 60Hz
- HDTV Standard: Full HD
- Hoods: molded
- Packaging: Polybag
- Wire material: CU
- Length: 3 m
- Shielding: Double shielding

Logistics

| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|-----------------|
| Packaging Unit Carton | 40 | 15.30 | 39.00 | 30.00 | 30.00 | 35,100.00 |
| Packaging Unit Inside | 10 | 3.83 | 35.00 | 34.00 | 10.00 | 11,900.00 |
| Packaging Unit Single | 1 | 0.38 | 16.00 | 14.00 | 4.00 | 896.00 |
| Net single without Packaging | 1 | 0.38 | 16.00 | 14.00 | 4.00 | 0.00 |

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany

<https://www.assmann.com>
info@assmann.com