DIGITUS® SATA connection cable

AK-400104-005-R

EAN 4016032299530



SATA connection cable, L-type F/F, 0.5m, 90ø l-angled - straight, SATAII/III, re

This internal data cable used to connect Serial-ATA Hard Drives as well as CD-/DVD/Blue-Ray Recorder to the Mainboard, for example. Because of the 90 ° left angled connector, the cable runs upward from the horizontally built-in hard drive. It's also downward compatible to SATA rev. II/I

Less thermic jam in the PC

- Compatible with Serial ATA standards
- Data transfer rate up to 300MB/s
- 7-wired cable, UL21149
- 4 x Data wires, 3 x earthing wires
- Male connector 90° angled

Attributes

- Asortiman: SATA kabeli
- Blokiranje: nema
- Brzina podataka: 6 Gbit/s
- Inačica: SATA Revizija 3
- Kabel u boji: crveni
- Kapice: ukalupljeno
- Konektor 1: SATA (7 polni) konektor, pod kutom od 90°, L-tip
- Konektor 2: SATA (7 polni) konektor, L-tip
- Konektor u boji: crni
- Vrsta: Ravni kabel
- Duljina: 0.5 m

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	300	6.10	46.00	32.00	25.00	36,800.00
Packaging Unit Inside	10	0.20	19.00	16.00	5.00	1,520.00
Packaging Unit Single	1	0.02	15.00	6.00	2.50	225.00
Net single without Packaging	1	0.01	12.50	3.50	2.00	0.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com