DIGITUS® SATA connection cable

AK-400102-003-R

EAN 4016032299943



SATA connection cable, L-type, w/ latch F/F, 0.3m, straight, SATA II/III, re

This internal data cable used to connect Serial-ATA Hard Drives as well as CD-/DVD/Blue-Ray Recorder to the Mainboard, for example. It's also downward compatible to SATA rev. II/I

With latch for a secure connection

- Compatible with Serial ATA standards
- 7-wired cable, UL21149
- 2 fixing angles included
- Provides a safe connection between hard disk and mainboard
- Provides a safe connection between hard disk and mainboard

Attributes

- Ambalaža: Polybag
- Asortiman: SATA kabeli
- AWG: 26
- Blokiranje: Metalni zasun
- Brzina podataka: 6 Gbit/s
- Inačica: SATA Revizija 3
- Kabel u boji: crveni
- Kapice: ukalupljeno
- Konektor 1: SATA (7 polni) konektor, L-tip
- Konektor 2: SATA (7 polni) konektor, L-tip
- Konektor u boji: crni
- Materijal žice: CU
- Vrsta: Ravni kabel
- Duljina: 0.3 m
- oklop: bez oklopa

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	300	4.50	46.00	32.00	25.00	36,800.00
Packaging Unit Inside	10	0.15	13.00	5.50	17.00	1,215.50
Packaging Unit Single	1	0.02	9.50	0.50	15.00	71.25
Net single without Packaging	1	0.01	8.20	2.00	1.30	0.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com