

# Digitus® Datatransfer extension cable, D-Sub25/M - D-Sub25/F

AK-610201-030-E

EAN 4016032301202



**Datatransfer extension cable, D-Sub25 M/F, 3.0m, serial/parallel, molded, be**

Datatransfer extension cable, D-Sub25,M/F, 3.0m, serial/parallel, molded, be

**Enables a save and stable connection**

#### Attributes

- Assignment: 1:1
- Assortment: Serial and Parallel Adapters
- AWG: 28

- Cable type: 25-wire
- Color cable: beige
- Color connector: beige
- Connector 1: DSUB, 25-pin, plug
- Connector 2: DSUB, 25-pin, jack
- Connector surface: nickel-plated
- Hoods: molded
- Packaging: Polybag
- Wire material: CU
- Length: 3 m
- Shielding: single shielding

| Logistics                           |              |             |            |            |             |                 |
|-------------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                                     | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| <b>Packaging Unit Carton</b>        | 40           | 16.40       | 35.00      | 22.00      | 38.00       | 29,260.00       |
| <b>Packaging Unit Inside</b>        | 10           | 4.10        | 36.00      | 36.00      | 13.00       | 16,848.00       |
| <b>Packaging Unit Single</b>        | 1            | 0.41        | 27.00      | 15.00      | 5.00        | 2,025.00        |
| <b>Net single without Packaging</b> | 1            | 0.30        | 15.50      | 15.00      | 4.50        | 0.00            |

#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)