# DIGITUS® Frame set for Keystone Modules

**AN-25178**

**EAN 4016032302261**



**Frame set, 2-level for 6x Keystone Jacks suitable for OBO-Ackermann GES6**

The DIGITUS® Frame sets function as adapter for the installation of Keystone Modules. They are available as 2-level version for 6x Keystone Modules or as 3-level version for 9x Keystone Modules.

**Frame set suitable for Ackermann GES 2, 4, 6, R4, R7**

- Layout keystone entry: 45° outlet
- Area of application: Floor box
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- Suitable for GES 2, GES 4, GES 4/10, GESR 4, GES 6, GES 6/10, GESR 8/10
- Frame suitable for installation in Ackermann floor box (OBO Bettermann underfloor systems)
- Plug direction of module 45° vertical
- Technical properties:
- Housing material: Metal
- Physical properties:
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)

**Logistics**

| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
|---|---|---|---|---|---|---|
| **Packaging Unit Carton** | 100 | 15.50 | 43.00 | 19.00 | 34.00 | 27,778.00 |
| **Packaging Unit Inside** | 10 | 1.55 | 8.00 | 18.00 | 17.00 | 2,448.00 |
| **Packaging Unit Single** | 1 | 0.16 | 3.00 | 10.00 | 29.00 | 870.00 |
| **Net single without Packaging** | 1 | 0.00 | 19.00 | 7.50 | 2.00 | 0.00 |

**More images:**



**Safety notes**

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com