

DIGITUS®

AK-440102-018-S

EAN 4016032311768



Power Cord, CEE 7/7 (Typ-F) - C13, 90° angled M/F, 1.8m, H05VV-F3G 0.75qmm, black

Digitus is a registered trademark of Digitus Technology Co., Ltd. All rights reserved. Digitus Technology Co., Ltd. is not responsible for any errors or omissions in this document. Digitus Technology Co., Ltd. reserves the right to change the specifications of the product without notice. Digitus Technology Co., Ltd. is not responsible for any damages or losses resulting from the use of this product. Digitus Technology Co., Ltd. is not responsible for any legal actions or claims against it. Digitus Technology Co., Ltd. is not responsible for any third-party claims against it. Digitus Technology Co., Ltd. is not responsible for any environmental or social issues. Digitus Technology Co., Ltd. is not responsible for any intellectual property rights. Digitus Technology Co., Ltd. is not responsible for any trademarks or logos. Digitus Technology Co., Ltd. is not responsible for any patents or copyrights. Digitus Technology Co., Ltd. is not responsible for any trade secrets or confidential information. Digitus Technology Co., Ltd. is not responsible for any data or information. Digitus Technology Co., Ltd. is not responsible for any software or hardware. Digitus Technology Co., Ltd. is not responsible for any services or products. Digitus Technology Co., Ltd. is not responsible for any other matters.

Attributes

- Assortment: Device Connection Cables
- Cable standard: H05 VV F3G
- Color cable: black
- Color connector: black

- Connector 1: CEE 7/7, plug
- Connector 2: IEC C13, jack
- Connector surface: nickel-plated
- Current load capacity: 250V/10A
- Hoods: molded
- Lead cross-section: 0.75qmm
- Packaging: Polybag
- Wire material: CU
- Length: 1.8 m
- Shielding: Unshielded

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	70	17.78	54.60	35.50	19.70	38,184.50
Packaging Unit Inside	10	2.54	50.00	40.00	4.00	8,000.00
Packaging Unit Single	1	0.25	19.00	14.00	16.00	4,256.00
Net single without Packaging	1	0.25	19.00	0.10	16.00	0.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com