# DIGITUS Cabo de ligação eléctrica

AK-440110-012-S EAN 4016032315131





#### Power Cord, CEE 7/7 (Typ-F) - C13 M/F, 1.2m, H05VVF3G 0.75qmm, black

Este cabo de rede serve para a ligação de um computador ou monitor à rede elétrica doméstica (tomada).

## Corresponde às normas alemãs

### Attributes

- Assortment: Device Connection Cables
- Cable standard: H05 VV F3G
- Color cable: black

- Color connector: black
- Connector 1: Schuko (CEE 7/7), plug
- Connector 2: IEC C13, jack
- Connector surface: nickel-plated
- Current load capacity: 250V/10A
- Hoods: molded
- Lead cross-section: 0.75qmm
- Packaging: Polybag
- Wire material: CU
- Length: 1.2 m
- Shielding: Unshielded

# Logistics

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	16.10	50.00	32.50	23.00	37,375.00
Packaging Unit Inside	10	1.61	21.00	22.00	10.50	4,851.00
Packaging Unit Single	1	0.16	4.00	18.00	18.00	1,296.00
Net single without Packaging	1	0.14	16.00	16.00	3.50	0.00

#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com

1