

DIGITUS® ASSNET100 " " U-

ACU-4511-305

EAN 4016032317081



ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey

ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey

ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey

- ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey
- ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey
- ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey
- ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey
- ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey
- ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey
- ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey
- ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey

- ASSNET100 CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey

Attributes

- Assortment: Twisted Pair Installation Cables
- Shielding: U-UTP, unshielded
- CPR: Eca
- Length: 305 m
- Color: grey
- Jacket: PVC
- Structure: 4 x 2 AWG 23/1, solid twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	2	8.58	36.00	34.00	28.00	34,272.00
Packaging Unit Inside	1	4.29	20.00	35.00	35.50	24,850.00
Packaging Unit Single	1	4.29	20.00	35.00	35.50	24,850.00
Net single without Packaging	1	8.58	0.00	0.00	0.00	0.00

More images:



DIGITUS

100 MHz
1 Gbit Ethernet
AWG 23/1

CAT 5e
20+/140°
Eca
CFR class

**ASSNET100
CAT 5e U/UTP Installation Cable,
305 m, Simplex, E_{ca}**

DIGITUS

ACU-4511-305 // ASSNET100 CAT 5e U/UTP Installation Cable, 305m, Simplex, E_{ca}

Anwendungsbeispiel
Example of use

DIGITUS

ACU-4511-305 // ASSNET100 CAT 5e U/UTP Installation Cable, 305m, Simplex, E_{ca}

Kabelquerschnitt
Cable cross section

Aufbauweise
140er Jacket

Cu-Drain
Cu-Wire

Aluminium
Control cable

DIGITUS

Produktdaten Product Information		Physikalische Spezifikationen Physical Properties	
Artikelnummer Part Number	100001-1	Umfang Scope	Kategorie Category
Hersteller Manufacturer	ASSMANN	Lebensdauer Lifetime	Material Material
Bestellnummer Order Number	100001-1	Temperaturbereich Temperature Range	Wegmaße Dimensions
Produktbeschreibung Product Description	ASSNET100 CAT 5e U/UTP Installation Cable, 305m, Simplex, E _{ca}	Spezifikationen Specifications	Abmessungen Dimensions
Technische Eigenschaften Technical Properties	<ul style="list-style-type: none"> 100 MHz 1 Gbit Ethernet AWG 23/1 E_{ca} CFR class 	<ul style="list-style-type: none"> 100 MHz 1 Gbit Ethernet AWG 23/1 E_{ca} CFR class 	<ul style="list-style-type: none"> 100 MHz 1 Gbit Ethernet AWG 23/1 E_{ca} CFR class

DIGITUS

Leistungseigenschaften Transmission Properties

PROZ.	MTT	MEZ	PE-MEZ	ACS	PE-ACS	IL	RL/EXT	PE-EXT
1	3	0	17	17	14	19	0,0	0,0
10	12	0,6	24	24	20	19	0,0	0,0
20	13	0,7	26	26	21	19	0,0	0,0
30	13	0,7	26	26	21	19	0,0	0,0
40	13	0,7	26	26	21	19	0,0	0,0
50	13	0,7	26	26	21	19	0,0	0,0
60	13	0,7	26	26	21	19	0,0	0,0
70	13	0,7	26	26	21	19	0,0	0,0
80	13	0,7	26	26	21	19	0,0	0,0
90	13	0,7	26	26	21	19	0,0	0,0
100	13	0,7	26	26	21	19	0,0	0,0

Bestandteile 100001-1 (ASSNET100 CAT 5e U/UTP Installation Cable, 305m, Simplex, E_{ca})

DIGITUS

DIGITUS

CFR-Bestimmungen Regulatory Requirements	Bestimmungen Requirements	Leistungseigenschaften (dB) Transmission Properties (dB)	Adaptation an verschiedene Umgebungen Adaptation to different environments	Spezifikationen Specifications
BZ _{ca}	Highly Very high	1+	• Typischerweise • Standard • Hohe Flexibilität • Hohe Flexibilität • Hohe Flexibilität	S
C _{ca}	High High	3	• Typischerweise • Standard • Hohe Flexibilität • Hohe Flexibilität	d
D _{ca}	Medium Medium	3	• Typischerweise • Standard • Hohe Flexibilität • Hohe Flexibilität	a
E _{ca}	Low Low	3	• Typischerweise • Standard • Hohe Flexibilität • Hohe Flexibilität	a

Bestandteile
100001-1



Safety notes

- Data cables must not be bent, stretched or twisted excessively. Sharp bends can damage the cable sheath and lead to failures or short circuits.
- Installation only by trained specialists.
- Installation only in dry rooms.
- The data cable must not be in direct contact with other electrical cables or high-voltage sources in order to avoid electromagnetic interference.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com