

# DIGITUS® CAT 6 S/FTP patch cable

DK-1644-020/BL  
EAN 4016032321743



### CAT 6 S-FTP patch cord, Cu, LSZH AWG 27/7, length 2 m, color black

DIGITUS® CAT 6 S-FTP patch cord, Cu, LSZH AWG 27/7, length 2 m, color black. This cable is designed for high-speed data transmission and is compliant with ISO/IEC 11801 and TIA/EIA 568 standards. It features a 250 MHz bandwidth and is suitable for applications requiring high performance and reliability. The cable is constructed with a 4 x 2 AWG 27/7 twisted pair structure and is shielded with S-FTP technology. The length is 2 meters and the color is black. The cable is packaged in a blister pack.





- 2 RJ45 (8P8C)
- 250 MHz bandwidth
- 4 x 2 AWG 27/7, twisted pair
- Shielding: S-FTP, pairs in metal foil and braid shielding

- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: Blister Pack
- Category: CAT 6
- Length: 2 m
- Color: black
- Jacket: LSOH
- Slim Version: no
- Structure: 4 x 2 AWG 27/7, twisted pair
- Flat Version: no

### Attributes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	8.00	40.00	31.00	30.00	37,200.00
Packaging Unit Inside	10	0.80	12.00	30.00	36.00	12,960.00
Packaging Unit Single	1	0.08	1.60	14.00	25.00	560.00
Net single without Packaging	1	0.07	200.00	1.20	1.30	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)