

Digitus® HDMI High Speed with Ethernet Connection Cable

AK-330115-010-S

EAN 4016032323006

**HDMI High Speed Connection Cable, Type D - Type A M/M, 1.0m, w/Ethernet, Full HD, 4K@30Hz, gold, bl**

This Full HD and 3D supporting cable is used for the connection of audio/video devices with a HDMI type D interface, which often is used by mobile devices such as Smart Phones of newest generation. Also capable for use of any IP-based application.

Supports Full HD and 3D and provides Ethernet connectivity.

- Support up to 4K with 30Hz
- HDMI-Standard: 1.4

Attributes

- Assortment: HDMI Cables
- AWG: 32

- Color cable: black
- Color connector: black
- Connector 1: HDMI type D (micro), plug
- Connector 2: HDMI type A, plug
- Connector surface: gold-plated
- Ferrite filter: none
- HDMI Standard: High Speed HDMI with Ethernet
- HDTV Standard: Full HD
- Hoods: molded
- Resolution max.: 3840 x 2160 Pixel, 30Hz
- Length: 1m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

| Logistics | | | | | | |
|-------------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 100 | 7.20 | 31.00 | 30.00 | 38.00 | 35,340.00 |
| Packaging Unit Inside | 10 | 0.72 | 46.00 | 40.00 | 5.00 | 9,200.00 |
| Packaging Unit Single | 1 | 0.07 | 24.00 | 17.00 | 2.00 | 816.00 |
| Net single without Packaging | 1 | 0.00 | 13.00 | 9.00 | 2.00 | 0.00 |

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com