


# Digitus® RS 232 adapter

AK-610517-000-I

EAN 4016032325109

**Adaptor, DB9, RJ45, Modular DB9 M, RJ45 F**

RS 232 to RJ45 adapter for self assembling

**For selfassembling**

- DSUB9, plug <=> RJ45, jack
- DSUB, 9-pin, with hex-screws
- PVC housing, color beige

**Attributes**

- Assortment: Serial and Parallel Adapters
- Cable type: 9-wire
- Color cable: beige
- Connector 1: DSUB, 9-pin, plug
- Hoods: plastic
- Length: 0.2 m

**Logistics**

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	500	10.31	45.00	35.00	35.00	55,125.00
Packaging Unit Inside	10	0.21	40.00	32.00	8.00	10,240.00
Packaging Unit Single	1	0.02	19.00	10.00	1.00	190.00
Net single without Packaging	1	0.00	9.00	3.50	1.50	0.00

**More images:**

**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)