

DIGITUS® DisplayPort

AK-340103-030-S
EAN 4016032328513



DisplayPort connection cable, DP M/M, 3.0m, w/interlock, DP, 1.1a conform, bl

DisplayPort standard: DisplayPort 1.1a
 Ferrite filter: none
 Resolution max.: 1920 x 1080 Pixel, 60Hz
 Length: 3 m
 AOC - Active Optical Cable: no
 Shielding: Double shielding

- Full HD 1080


Attributes

- Assortment: DisplayPort Cables
- Color cable: black
- Color connector: black
- Connector 1: DP, plug

- Connector 2: DP, plug
- Connector surface: nickel-plated
- Hoods: molded
- Interlock: Snap fastener
- Resolution max.: 1920 x 1080 Pixel, 60Hz
- Length: 3 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	50	8.30	22.00	31.00	55.00	37,510.00
Packaging Unit Inside	10	1.66	7.00	31.00	35.00	7,595.00
Packaging Unit Single	1	0.17	20.00	14.00	3.00	840.00
Net single without Packaging	1	0.17	20.00	14.00	3.00	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com