

# DIGITUS® DisplayPort

AK-340410-001-S  
EAN 4016032328582



**DisplayPort adapter cable, DP - HD15 M/F, 0.15m,w/interlock, DP 1.1a compatible, CE, bl**

**Digitus DisplayPort adapter cable, DP - HD15 M/F, 0.15m,w/interlock, DP 1.1a compatible, CE, bl**

- 1080p 60 Hz

**Attributes**

- Assortment: DisplayPort Cables
- AWG: 34
- Color cable: black
- Color connector: black

- Connector 1: DP, plug
- Connector 2: HD15, jack
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Length: 0.15 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	4.00	46.00	35.00	27.00	43,470.00
Packaging Unit Inside	10	0.40	27.00	27.00	11.00	8,019.00
Packaging Unit Single	1	0.04	23.00	16.00	2.50	920.00
Net single without Packaging	1	0.03	1.00	3.70	17.80	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)