

# DIGITUS® UAE Cabo de ligação em espiral modular

AK-460101-020-S

EAN 4016032330110



**Cabo de ligação UAE, RJ10 St/St, 2.0m, CU, 4x7x0.12mm, plano, helic, sw**

Este cabo modular em espiral pode ser utilizado para ligar o microtelefone ao telefone e é um substituto ideal para os cabos originais do microtelefone que são demasiado curtos/longos ou estão defeituosos.

**Altamente elástico e flexível**

- Ficha modular RJ10, 4P4C <=> Ficha modular RJ10, 4P4C

- Tampão de plástico, transparente
- Atribuição: 1:1
- Cabo em espiral de 4 núcleos
- Cor: preto

#### Attributes

- Assortment: Telecommunication Cables
- Length: 2 m

#### Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
<b>Packaging Unit Carton</b>	400	13.33	44.50	40.00	26.00	46,280.00
<b>Packaging Unit Inside</b>	10	0.33	19.50	13.50	6.00	1,579.50
<b>Packaging Unit Single</b>	1	0.03	1.50	14.00	20.00	420.00
<b>Net single without Packaging</b>	1	0.03	38.00	5.00	1.10	0.00

#### More images:



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)