

DIGITUS® DisplayPort, 15m

AK-340100-150-S
EAN 4016032330776



Displayport connection cable, DP M/M, 15.0m, w/interlock, Full HD 1080p, bl

Digitus DisplayPort connection cable, DP M/M, 15.0m, w/interlock, Full HD 1080p, bl. This cable is designed for high-quality video and audio transmission. It features a robust interlocking design to prevent accidental disconnection. The cable is compatible with a wide range of devices, including CAD/CAM, GIS, and 3D applications. The connectors are made of high-quality materials and are nickel-plated for durability. The cable is triple-shielded to minimize interference and ensure clear signal transmission. The length is 15 meters, providing flexibility in setup. The cable is packaged in a polybag for protection. The wire material is copper (CU). The ferrite filter is none. The HDTV standard is 1080p. The interlock is a snap fastener. The packaging is a polybag. The color of the cable is black. The connector color is black. The connector 1 is a DP plug. The connector 2 is a DP plug. The connector surface is nickel-plated. The cable is suitable for use in various environments, including industrial settings. The cable is made of high-quality materials and is designed for long-term use. The cable is compatible with a wide range of devices, including CAD/CAM, GIS, and 3D applications. The cable is triple-shielded to minimize interference and ensure clear signal transmission. The length is 15 meters, providing flexibility in setup. The cable is packaged in a polybag for protection. The wire material is copper (CU). The ferrite filter is none. The HDTV standard is 1080p. The interlock is a snap fastener. The packaging is a polybag. The color of the cable is black. The connector color is black. The connector 1 is a DP plug. The connector 2 is a DP plug. The connector surface is nickel-plated.

- Support 1080p with 30Hz
- Max. supported Video Resolution: 1920 x 1080 p with 60 Hz
- Supported transmission modes: RBR, HBR, HBR2
- HDCP-Version: HDCP 1.3

Attributes

- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black

- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- Ferrite filter: none
- HDTV Standard: 1080p
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 15 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	9.20	36.50	33.00	20.00	24,090.00
Packaging Unit Inside	1	0.92	7.00	22.00	28.50	4,389.00
Packaging Unit Single	1	0.92	19.00	19.00	5.00	1,805.00
Net single without Packaging	1	0.92	7.00	22.00	28.50	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com