

# DIGITUS® DIGITUS Unique - 600 x 600 x 600 Unique - 600 x 600 x 600

DN-19 26U-6/6-1  
EAN 4016032331131



### 26U network rack, Unique 1342x600x600 mm, color grey (RAL 7035)

The DIGITUS Unique network cabinet is a 26U rack with a depth of 600 mm and a width of 600 mm. It is made of light grey (RAL 7035) steel. The cabinet has a glass front door and a steel rear door with cable entry. It is designed for easy installation and maintenance.

- IP protection class: IP20
- Front door: Glass door, single opening
- Rear door: Steel door and cable entry, single opening
- Side panels: Both sides
- Units: 26
- Width: 600 mm
- Depth: 600 mm
- Height: 1342 mm
- IP protection class: IP20
- Mounted: yes
- Package contents:
  - Earthing cable set
  - Installation set (screws, cage nuts, washers)
  - 2 x key
  - 4 x leveling foot, M10

- Cabinet type: Network cabinet
- Color: light grey, RAL 7035
- Load capacity: 1200 kg
- Front door: Glass door, single opening
- Rear door: Steel door and cable entry, single opening
- Side panels: Both sides
- Units: 26
- Width: 600 mm
- Depth: 600 mm
- Height: 1342 mm
- IP protection class: IP20
- Mounted: yes
- Package contents:
  - Earthing cable set
  - Installation set (screws, cage nuts, washers)
  - 2 x key
  - 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	53.70	65.00	65.00	139.20	588,120.00
Packaging Unit Inside	1	53.70	65.00	65.00	139.20	588,120.00
Packaging Unit Single	1	53.70	65.00	65.00	139.20	588,120.00
Net single without Packaging	1	52.70	60.00	60.00	134.20	0.00

**More images:**



**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)