

DIGITUS® Unique DIGITUS – 800 x 800

DN-19 32U-8/8-1

EAN 4016032331162



32U network rack, Unique 1609x800x800 mm, color grey (RAL 7035)

The DIGITUS Unique 32U network rack is designed for high-density server and network equipment. It features a robust steel frame and a glass front door for easy access to the equipment. The rack is available in light grey (RAL 7035) and is suitable for indoor use.

- Protection class: IP20
- Front door: Glass door, single opening (180° opening)
- Rear door: Steel door and cable entry, double opening
- Load capacity: 1200 kg
- Side panels: Both sides
- Units: 32
- Depth: 800 mm
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes
- Package contents:
 - Forming cable set
 - Installation set (screws, cage nuts, washers)
 - 2 x key
 - 4 x leveling foot, M10

The rack is designed for high-density server and network equipment. It features a robust steel frame and a glass front door for easy access to the equipment. The rack is available in light grey (RAL 7035) and is suitable for indoor use.

- Color: light grey, RAL 7035
- Depth: 800 mm
- Front door: Glass door, single opening
- Load capacity: 1200 kg
- Rear door: Steel door and cable entry, double opening
- Side panels: Both sides
- Units: 32
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes
- Package contents:
 - Forming cable set
 - Installation set (screws, cage nuts, washers)
 - 2 x key
 - 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	97.00	85.00	85.00	165.90	1,198,630.00
Packaging Unit Inside	1	97.00	85.00	85.00	165.90	1,198,630.00
Packaging Unit Single	1	97.00	85.00	85.00	165.90	1,198,630.00
Net single without Packaging	1	96.00	80.00	80.00	160.90	0.00

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
 info@assmann.com