

# DIGITUS® DIGITUS Unique - 600 x 1000

DN-19 26U-6/10-1  
EAN 4016032332251



## 26U network rack, Unique 1342x600x1000 mm, color grey (RAL 7035)

The DIGITUS Unique 26U network rack is a high-quality, industrial-grade cabinet designed for housing network equipment. It features a robust steel construction and a light grey finish (RAL 7035). The cabinet is 1342 mm deep, 600 mm wide, and 1000 mm high. It is designed to accommodate 26 U-rack units. The front door is made of glass, providing a clear view of the equipment inside, while the rear door is made of steel and includes a cable entry system. The cabinet is equipped with side panels on both sides and is mounted on four leveling feet. It is suitable for indoor use and has an IP20 protection class. The cabinet is available in two depths: 1000 mm and 1342 mm. The 1342 mm depth is the standard configuration. The cabinet is designed to be easy to install and maintain. It is suitable for use in a variety of environments, including data centers, server rooms, and network closets. The cabinet is made of high-quality steel and is finished with a durable powder coating. It is designed to be fire-resistant and to provide excellent protection against dust and debris. The cabinet is also designed to be easy to transport and handle. It is suitable for use in a variety of environments, including data centers, server rooms, and network closets. The cabinet is made of high-quality steel and is finished with a durable powder coating. It is designed to be fire-resistant and to provide excellent protection against dust and debris. The cabinet is also designed to be easy to transport and handle.

- IP protection class: IP20
- Front door: Glass door, single opening
- Rear door: Steel door and cable entry, single opening
- Side panels: Both sides
- Units: 26
- Width: 600 mm
- Depth: 1342 mm
- IP protection class: IP20
- Mounted: yes
- Package contents
  - Earthing cable set
  - Installation set (screws, cage nuts, washers)
  - 2 x key
  - 4 x leveling foot, M10

- Cabinet type: Network cabinet
- Color: light grey, RAL 7035
- Front door: Glass door, single opening
- Load capacity: 1200 kg
- Rear door: Steel door and cable entry, single opening
- Side panels: Both sides
- Units: 26
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes
- Package contents
  - Earthing cable set
  - Installation set (screws, cage nuts, washers)
  - 2 x key
  - 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	78.00	105.00	65.00	139.20	950,040.00
Packaging Unit Inside	1	78.00	105.00	65.00	139.20	950,040.00
Packaging Unit Single	1	78.00	105.00	65.00	139.20	950,040.00
Net single without Packaging	1	77.00	100.00	60.00	134.20	0.00

**More images:**



**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)