

DIGITUS® Unique DIGITUS – 800 x 800

DN-19 36U-8/8-1
EAN 4016032332329



36U network rack, Unique 1787x800x800 mm, color grey (RAL 7035)

DIGITUS Unique 36U network rack, 1787x800x800 mm, color grey (RAL 7035), load capacity 1200 kg, depth 800 mm, front door glass, rear door steel, side panels both sides, units 36, width 800 mm, IP protection class IP20, mounted yes, forming cable set, installation set (screws, cage nuts, washers), 2 x key, 4 x leveling foot, M10.

DIGITUS® Unique 36U network rack, 1787x800x800 mm, color grey (RAL 7035), load capacity 1200 kg, depth 800 mm, front door glass, rear door steel, side panels both sides, units 36, width 800 mm, IP protection class IP20, mounted yes, forming cable set, installation set (screws, cage nuts, washers), 2 x key, 4 x leveling foot, M10.

- IP protection class: IP20
- Front door: Glass door, single opening
- Load capacity: 1200 kg
- Rear door: Steel door, closed, double opening
- Side panels: Both sides
- Units: 36
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes
- Forming cable set
- Installation set (screws, cage nuts, washers)
- 2 x key
- 4 x leveling foot, M10

Unique 36U network rack, 1787x800x800 mm, color grey (RAL 7035), load capacity 1200 kg, depth 800 mm, front door glass, rear door steel, side panels both sides, units 36, width 800 mm, IP protection class IP20, mounted yes, forming cable set, installation set (screws, cage nuts, washers), 2 x key, 4 x leveling foot, M10.

Unique 36U network rack, 1787x800x800 mm, color grey (RAL 7035), load capacity 1200 kg, depth 800 mm, front door glass, rear door steel, side panels both sides, units 36, width 800 mm, IP protection class IP20, mounted yes, forming cable set, installation set (screws, cage nuts, washers), 2 x key, 4 x leveling foot, M10.

- Depth: 800 mm
- Front door: Glass door, single opening
- Load capacity: 1200 kg
- Rear door: Steel door, closed, double opening
- Side panels: Both sides
- Units: 36
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes
- Forming cable set
- Installation set (screws, cage nuts, washers)
- 2 x key
- 4 x leveling foot, M10

Package contents

- Forming cable set
- Installation set (screws, cage nuts, washers)
- 2 x key
- 4 x leveling foot, M10

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|--------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 1 | 97.00 | 85.00 | 85.00 | 183.70 | 1,327,230.00 |
| Packaging Unit Inside | 1 | 97.00 | 85.00 | 85.00 | 183.70 | 1,327,230.00 |
| Packaging Unit Single | 1 | 97.00 | 85.00 | 85.00 | 183.70 | 1,327,230.00 |
| Net single without Packaging | 1 | 96.00 | 80.00 | 80.00 | 178.70 | 0.00 |

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com