

DIGITUS® DIGITUS Unique - 600 x 800

DN-19 42U-6/8-B-1
EAN 4016032332435



42U network rack, Unique 2053x600x800 mm, color black (RAL 9005)

The DIGITUS Unique network rack is a high-quality, professional-grade server cabinet. It is designed for reliable performance and easy maintenance. The cabinet is made of high-quality steel and is painted in a durable black finish (RAL 9005). It features a glass front door for easy access to the equipment inside. The rack is compatible with 42U of equipment and has a maximum load capacity of 1200 kg. It is available in two depths: 800 mm and 1000 mm. The cabinet is also available in a different color (RAL 7035) and is compatible with other rack types (e.g., 483 mm depth).

The DIGITUS Unique network rack is a high-quality, professional-grade server cabinet. It is designed for reliable performance and easy maintenance. The cabinet is made of high-quality steel and is painted in a durable black finish (RAL 9005). It features a glass front door for easy access to the equipment inside. The rack is compatible with 42U of equipment and has a maximum load capacity of 1200 kg. It is available in two depths: 800 mm and 1000 mm. The cabinet is also available in a different color (RAL 7035) and is compatible with other rack types (e.g., 483 mm depth).

- Protection class: IP20
- Front door: Glass door, single opening
- Rear door: Steel door and cable entry, single opening
- Side panels: Both sides
- Units: 42
- Width: 600 mm
- Depth: 800 mm / 1000 mm
- Load capacity: 1200 kg
- Mounted: yes
- IP protection class: IP20
- Package contents:
 - Earthing cable set
 - Installation set (screws, cage nuts, washers)
 - 2 x key
 - 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	91.00	85.00	65.00	210.30	1,161,910.00
Packaging Unit Inside	1	91.00	85.00	65.00	210.30	1,161,910.00
Packaging Unit Single	1	91.00	85.00	65.00	210.30	1,161,910.00
Net single without Packaging	1	91.00	80.00	60.00	205.30	0.00

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com