

DIGITUS® Acoplamento simplex ST / ST, multimodo

DN-96002-1

EAN 4016032335610



Acoplamento de fibra ótica, simplex, ST para ST, MM Casquilho de cerâmica, caixa metálica, proteção preta contra o pó

Os acopladores de fibra ótica de alta qualidade da DIGITUS® com virola de cerâmica são o complemento perfeito para a montagem de caixas de emenda. Graças a controlos de qualidade constantes e a um fabrico preciso, os acopladores garantem um desempenho e uma qualidade de ligação óptimos. Cada acoplador está equipado com um tampão de pó para proteger as virolas da contaminação. Além disso, os acoplamentos são fornecidos com os acessórios de fixação adequados para que possam ser imediatamente inseridos e fixados nos painéis frontais. O desempenho ótimo é alcançado através da utilização de pigtails DIGITUS®, que são

fabricados com a mesma elevada qualidade e cujos conectores interagem perfeitamente com os acopladores.

A solução ideal para caixas de emenda

- ST / ST
- Simplex
- Caixa metálica
- Manga de cerâmica
- Multimodo
- Tampas de pó pretas
- Incl. material de montagem

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1500	16.50	40.00	28.00	25.00	28,000.00
Packaging Unit Inside	50	0.55	1.50	22.00	16.00	528.00
Packaging Unit Single	1	0.01	1.50	1.50	2.00	4.50
Net single without Packaging	1	0.02	1.50	0.90	3.00	0.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com