

DIGITUS® Network cabinet Unique series - 600x600 mm (WxD)

DN-19 32U-6/6-B-1
EAN 4016032337959



32U network rack, Unique 1609x600x600 mm, color black (RAL 9005)

The Digitus Unique series network cabinet is a high-quality, professional-grade cabinet designed for network equipment. It features a robust steel construction and a glass front door for easy access to the equipment. The cabinet is available in two colors: black (RAL 7035) and black (RAL 9005). The cabinet is designed to hold up to 32 units and has a depth of 600 mm. The cabinet is also equipped with a rear door and cable entry for easy cable management. The cabinet is also equipped with a front door and a single opening. The cabinet is also equipped with a load capacity of 1200 kg. The cabinet is also equipped with side panels on both sides. The cabinet is also equipped with 2 keys and 4 leveling feet (M10).

The Digitus Unique series network cabinet is a high-quality, professional-grade cabinet designed for network equipment. It features a robust steel construction and a glass front door for easy access to the equipment. The cabinet is available in two colors: black (RAL 7035) and black (RAL 9005). The cabinet is designed to hold up to 32 units and has a depth of 600 mm. The cabinet is also equipped with a rear door and cable entry for easy cable management. The cabinet is also equipped with a front door and a single opening. The cabinet is also equipped with a load capacity of 1200 kg. The cabinet is also equipped with side panels on both sides. The cabinet is also equipped with 2 keys and 4 leveling feet (M10).

- IP20
 - Front door: Glass door, single opening
 - Load capacity: 1200 kg
 - Rear door: Steel door and cable entry, single opening
 - Side panels: Both sides
 - Units: 32
 - Width: 600 mm
 - IP protection class: IP20
 - Mounted: yes
- Package contents**
- Earthing cable set
 - Installation set (screws, cage nuts, washers)
 - 2 x key
 - 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	61.90	65.00	65.00	165.90	700,928.00
Packaging Unit Inside	1	61.90	65.00	65.00	165.90	700,928.00
Packaging Unit Single	1	61.90	65.00	65.00	165.90	700,928.00
Net single without Packaging	1	60.90	60.00	60.00	160.90	0.00

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com