

# DIGITUS® Network cabinet Unique series - 800x1000 mm (WxD)

DN-19 26U-8/10-1  
 EAN 4016032341161



## 26U network rack, Unique 1342x800x1000 mm, color grey (RAL 7035)


The DIGITUS Unique series network cabinet is designed for high-density network equipment. It features a depth of 1000 mm and a width of 800 mm. The cabinet is available in light grey (RAL 7035) and is suitable for environments with a temperature range of -10°C to 40°C. It is designed to hold up to 26 U of equipment and has a load capacity of 1200 kg.

The DIGITUS Unique series network cabinet is designed for high-density network equipment. It features a depth of 1000 mm and a width of 800 mm. The cabinet is available in light grey (RAL 7035) and is suitable for environments with a temperature range of -10°C to 40°C. It is designed to hold up to 26 U of equipment and has a load capacity of 1200 kg.

- Protection class: IP20
  - Temperature range: -10°C to 40°C
  - Humidity range: 5% to 95% (non-condensing)
  - Door opening: 120°
  - Lock: Key lock
  - Cable management: Cable tray, cable duct
  - Mounting: 4 mounting holes
  - Depth: 1000 mm
  - Front door: Glass door, single opening
  - Load capacity: 1200 kg
  - Rear door: Steel door and cable entry, double opening
  - Side panels: Both sides
  - Units: 26
  - Width: 800 mm
  - IP protection class: IP20
  - Mounted: yes
- Package contents**
- Earthing cable set
  - Installation set (screws, cage nuts, washers)
  - 2 x key
  - 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	89.00	105.00	85.00	139.20	1,242,360.00
Packaging Unit Inside	1	89.00	105.00	85.00	139.20	1,242,360.00
Packaging Unit Single	1	89.00	105.00	85.00	139.20	1,242,360.00
Net single without Packaging	1	88.00	100.00	80.00	134.20	0.00

**More images:**



**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)