

DIGITUS® LC Keystone Adapter for Patch Panel

DN-BLIND-LC

EAN 4016032342274



LC keystone frame for patch panel color white

The DIGITUS® Snap-in adapters for Patch Panel offer you the easiest solution to expand empty fields of your Patch Panel or to cover them. The LC Keystone frames contains a slot in each case for LC plugs and are therefore optimal to optimize the cabling of your Patch Panel. All

DIGITUS® Snap-in adapters are available in the colors grey or black. Also available are special LC couplers without flanks.

The fiber optic solution for your modular Patch Panels

- Keystone frame for LC couplers
- Color: white

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 5000 | 9.50 | 50.00 | 33.00 | 35.00 | 57,750.00 |
| Packaging Unit Inside | 100 | 0.19 | 17.00 | 10.00 | 5.00 | 850.00 |
| Packaging Unit Single | 1 | 0.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Net single without Packaging | 1 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |

More images:



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage

- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com