

# DIGITUS® Unique DIGITUS – 800 x 800

DN-19 32U-8/8-B-1  
EAN 4016032343394



### 32U network rack, Unique 1609x800x800 mm, color black (RAL 9005)

The DIGITUS Unique network rack is a high-quality, professional-grade server cabinet. It is designed for use in data centers and server rooms. The rack is made of high-quality steel and is painted in a durable black finish (RAL 9005). It features a glass front door and a steel rear door. The rack is designed to hold up to 32 units and has a load capacity of 1200 kg. It also features a rear door with a double opening for cable entry and side panels on both sides. The rack is easy to install and is compatible with standard 19-inch equipment. The rack is also available in a 483 mm (19-inch) depth version.

The DIGITUS Unique network rack is a high-quality, professional-grade server cabinet. It is designed for use in data centers and server rooms. The rack is made of high-quality steel and is painted in a durable black finish (RAL 9005). It features a glass front door and a steel rear door. The rack is designed to hold up to 32 units and has a load capacity of 1200 kg. It also features a rear door with a double opening for cable entry and side panels on both sides. The rack is easy to install and is compatible with standard 19-inch equipment. The rack is also available in a 483 mm (19-inch) depth version.

- Protection class: IP20
- Front door: Glass door, single opening
- Rear door: Steel door and cable entry, double opening
- Side panels: Both sides
- Units: 32
- Depth: 800 mm
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes
- Package contents:
  - Earthing cable set
  - Installation set (screws, cage nuts, washers)
  - 2 x key
  - 4 x leveling foot, M10

- Color: black, RAL 9005
- Depth: 800 mm
- Front door: Glass door, single opening
- Load capacity: 1200 kg
- Rear door: Steel door and cable entry, double opening
- Side panels: Both sides
- Units: 32
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes
- Package contents:
  - Earthing cable set
  - Installation set (screws, cage nuts, washers)
  - 2 x key
  - 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	97.00	85.00	85.00	165.90	1,198,630.00
Packaging Unit Inside	1	97.00	85.00	85.00	165.90	1,198,630.00
Packaging Unit Single	1	97.00	85.00	85.00	165.90	1,198,630.00
Net single without Packaging	1	96.00	80.00	80.00	160.90	0.00

### Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.

- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)