

DIGITUS® Unique DIGITUS – 800 x 800

DN-19 22U-8/8-B-1
EAN 4016032344322



22U network rack, Unique 1164x800x800 mm, color black (RAL 9005)

The DIGITUS Unique network rack is a high-quality, industrial-grade cabinet designed for housing network equipment. It features a robust steel construction and a glass front door for easy access to the internal components. The rack is available in two cabinet types: Network Cabinet and Server Cabinet. The color is black (RAL 9005).

The DIGITUS Unique network rack is a high-quality, industrial-grade cabinet designed for housing network equipment. It features a robust steel construction and a glass front door for easy access to the internal components. The rack is available in two cabinet types: Network Cabinet and Server Cabinet. The color is black (RAL 9005).

- IP protection class: IP20
- Front door: Glass door, single opening
- Rear door: Steel door, closed, double opening
- Side panels: Both sides
- Units: 22
- Width: 800 mm
- Load capacity: 1200 kg
- IP protection class: IP20
- Mounted: yes
- Forming cable set
- Installation set (screws, cage nuts, washers)
- 2 x key
- 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	69.00	85.00	85.00	121.40	877,115.00
Packaging Unit Inside	1	69.00	85.00	85.00	121.40	877,115.00
Packaging Unit Single	1	69.00	85.00	85.00	121.40	877,115.00
Net single without Packaging	1	68.00	80.00	80.00	116.40	0.00

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com