DIGITUS® Fiber Optic 2 mm shrink splice protection, 45 mm

AL-SK6

EAN 4016032349297



Fiber Optic 2 mm Shrink Splice Protection 45 mm 1 mm stainless steel wire, 1 pc =1 tray w 100 pcs.

This Fiber Optic shrink splice protection is ideal to protect the splice from 2 fibers after the splicing. It shrinks to the fiber when you heat him.

- Keeps optical transmission properties of optical fiber
- Provides strength and protection to optical fiber splices
- Easy usage, avoid damages to the optical fiber
- Operating temperature: -45 °C up to +100 °C
- Packaging: 100 pcs

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	600	26.50	37.00	27.00	48.00	47,952.00
Packaging Unit Inside	12	0.53	7.00	18.50	27.00	3,496.50
Packaging Unit Single	1	0.04	2.00	5.50	6.00	66.00
Net single without Packaging	1	0.04	0.00	0.00	0.00	0.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com