

DIGITUS® Network cabinet Unique series - 800x800 mm (WxD)

DN-19 26U-8/8-1

EAN 4016032353515



26U network rack, Unique 1342x800x800 mm, color grey (RAL 7035)

Digitus Unique series network cabinets are designed for high performance and reliability. They feature a robust steel construction and a glass front door for easy access to the equipment. The cabinets are available in two colors: grey (RAL 7035) and white (RAL 9005). The cabinets are designed to hold up to 26 units and have a depth of 800 mm. The cabinets are also equipped with a rear door for cable management and a side panel for easy access to the equipment. The cabinets are also equipped with a locking mechanism for security.

Digitus® Unique series network cabinets are designed for high performance and reliability. They feature a robust steel construction and a glass front door for easy access to the equipment. The cabinets are available in two colors: grey (RAL 7035) and white (RAL 9005). The cabinets are designed to hold up to 26 units and have a depth of 800 mm. The cabinets are also equipped with a rear door for cable management and a side panel for easy access to the equipment. The cabinets are also equipped with a locking mechanism for security.

- Protection class: IP20
- Front door: Glass door, single opening
- Load capacity: 1200 kg
- Rear door: Steel door and cable entry, double opening
- Side panels: Both sides
- Units: 26
- Depth: 800 mm
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes
- Package contents
 - Earthing cable set
 - Installation set (screws, cage nuts, washers)
 - 2 x key
 - 4 x leveling foot, M10

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|--------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 1 | 82.00 | 85.00 | 85.00 | 139.20 | 1,005,720.00 |
| Packaging Unit Inside | 1 | 82.00 | 85.00 | 85.00 | 139.20 | 1,005,720.00 |
| Packaging Unit Single | 1 | 82.00 | 85.00 | 85.00 | 139.20 | 1,005,720.00 |
| Net single without Packaging | 1 | 81.00 | 80.00 | 80.00 | 134.20 | 0.00 |

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com