

# DIGITUS® Network cabinet Unique series - 800x800 mm (WxD)

DN-19 26U-8/8-1  
EAN 4016032353515



### 26U network rack, Unique 1342x800x800 mm, color grey (RAL 7035)

Digitus Unique series network cabinet is designed for housing network equipment. It features a depth of 800 mm, a width of 800 mm, and a height of 1342 mm. The cabinet is made of steel and is painted in a grey color (RAL 7035). It has a glass front door and a steel rear door with cable entry. The cabinet is suitable for 26U of equipment. The load capacity is 1200 kg. The cabinet is suitable for indoor use. The cabinet is suitable for use in a rack. The cabinet is suitable for use in a rack. The cabinet is suitable for use in a rack.

Digitus® Unique series network cabinet is designed for housing network equipment. It features a depth of 800 mm, a width of 800 mm, and a height of 1342 mm. The cabinet is made of steel and is painted in a grey color (RAL 7035). It has a glass front door and a steel rear door with cable entry. The cabinet is suitable for 26U of equipment. The load capacity is 1200 kg. The cabinet is suitable for indoor use. The cabinet is suitable for use in a rack. The cabinet is suitable for use in a rack. The cabinet is suitable for use in a rack.

- IP protection class: IP20
- Front door: Glass door, single opening
- Load capacity: 1200 kg
- Rear door: Steel door and cable entry, double opening
- Side panels: Both sides
- Units: 26
- Depth: 800 mm
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes
- Package contents
  - Earthing cable set
  - Installation set (screws, cage nuts, washers)
  - 2 x key
  - 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	82.00	85.00	85.00	139.20	1,005,720.00
Packaging Unit Inside	1	82.00	85.00	85.00	139.20	1,005,720.00
Packaging Unit Single	1	82.00	85.00	85.00	139.20	1,005,720.00
Net single without Packaging	1	81.00	80.00	80.00	134.20	0.00

**More images:**



**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)