

# DIGITUS® RS-232 to RS-485

DA-70161

EAN 4016032358480



### RS232 to RS485 Adapter transmission rate: 300-115.2 Kbps

Digitus RS-232 to RS-485 Adapter is a high-quality adapter that converts RS-232 to RS-485. It is designed for use in industrial environments and provides a reliable and secure connection between RS-232 and RS-485 devices. The adapter is compatible with RS-232 devices that support a transmission rate of 300-115200 bps/s. The adapter is made of high-quality materials and is designed to be durable and reliable. The adapter is easy to use and does not require any special software or drivers. The adapter is compatible with Windows (2000, 2003, 2008, XP, Vista, 7, 8), Mac & Linux.

### Compatible with RS-232 to RS-485.

- Complies with EIA and TIA
- Supports RS-232C and RS-485A protocols
- Supports RS-232C and RS-485A protocols
- Supports RS-232C and RS-485A protocols

- Transmission rate: 1200 (RS-485), 5 (RS-232)
- Operating temperature: -25 to 70 °C
- Dimensions: 17 x 55 x 64 mm
- Weight: 1.7 g
- Compatible with Windows (2000, 2003, 2008, XP, Vista, 7, 8), Mac & Linux

### Package contents

- 1 x RS-232 to RS-485 Adapter
- 1 x User Manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	150	13.35	50.00	22.00	47.00	51,700.00
Packaging Unit Inside	1	0.09	11.00	19.50	3.00	643.50
Packaging Unit Single	1	0.09	11.00	19.50	3.00	643.50
Net single without Packaging	1	0.03	6.30	3.30	1.70	0.00

### More images:



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)