

DIGITUS® Network cabinet Unique series - 800x1200 mm (WxD)

DN-19 42U-8/12-1
 EAN 4016032361879



42U network rack, Unique 2053x800x1200 mm, color grey (RAL 7035)

The DIGITUS Unique series network cabinet is designed for high-density network equipment. It features a robust steel construction and a glass front door for easy access to the internal components. The cabinet is available in two depth options: 483 mm (19") and 483 mm (19"). The cabinet is finished in light grey (RAL 7035) and is suitable for indoor use.

- Protection class: IP20
- Front door: Glass door, single opening
- Rear door: Steel door and cable entry, double opening
- Side panels: Both sides
- Units: 42
- Width: 800 mm
- Depth: 1200 mm
- Color: light grey, RAL 7035
- Mounted: yes
- Load capacity: 1200 kg
- IP protection class: IP20
- Package contents:
 - Earthing cable set
 - Installation set (screws, cage nuts, washers)
 - 2 x key
 - 4 x leveling foot, M10

- Color: light grey, RAL 7035
- Depth: 1200 mm
- Front door: Glass door, single opening
- Mounted: yes
- Load capacity: 1200 kg
- Rear door: Steel door and cable entry, double opening
- Side panels: Both sides
- Units: 42
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes
- Package contents:
 - Earthing cable set
 - Installation set (screws, cage nuts, washers)
 - 2 x key
 - 4 x leveling foot, M10

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	153.00	125.00	85.00	210.30	2,234,440.00
Packaging Unit Inside	1	153.00	125.00	85.00	210.30	2,234,440.00
Packaging Unit Single	1	153.00	125.00	85.00	210.30	2,234,440.00
Net single without Packaging	1	152.00	120.00	80.00	205.30	0.00

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com