

# DIGITUS® Network cabinet Unique series - 800x1200 mm (WxD)

DN-19 42U-8/12-1B  
 EAN 4016032364276



### 42U network rack, Unique 2053x800x1200 mm, color black (RAL 9005)

The DIGITUS Unique series network cabinet is designed for high-density server environments. It features a robust steel construction and a glass front door for easy access to the equipment. The cabinet is available in two depth options: 483 mm (19") and 483 mm (19"). The cabinet is finished in black (RAL 9005) and is suitable for indoor use.

The DIGITUS® Unique series network cabinet is designed for high-density server environments. It features a robust steel construction and a glass front door for easy access to the equipment. The cabinet is available in two depth options: 483 mm (19") and 483 mm (19"). The cabinet is finished in black (RAL 9005) and is suitable for indoor use.

- Protection class: IP20
  - Front door: Glass door, single opening
  - Rear door: Steel door and cable entry, double opening
  - Side panels: Both sides
  - Units: 42
  - Width: 800 mm
  - Depth: 1200 mm
  - Color: black, RAL 9005
  - Mounted: yes
  - Load capacity: 1200 kg
  - IP protection class: IP20
- Package contents**
- Earthing cable set
  - Installation set (screws, cage nuts, washers)
  - 2 x key
  - 4 x leveling foot, M10

| Logistics                    |              |             |            |            |             |              |
|------------------------------|--------------|-------------|------------|------------|-------------|--------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³          |
| Packaging Unit Carton        | 1            | 153.00      | 125.00     | 85.00      | 210.30      | 2,234,440.00 |
| Packaging Unit Inside        | 1            | 153.00      | 125.00     | 85.00      | 210.30      | 2,234,440.00 |
| Packaging Unit Single        | 1            | 153.00      | 125.00     | 85.00      | 210.30      | 2,234,440.00 |
| Net single without Packaging | 1            | 152.00      | 120.00     | 80.00      | 205.30      | 0.00         |

**More images:**



**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)